

PRODUCT SPECIFICATIONS **TraceNet[™] Command** APPLICATION SUITE

APPLICATION

TraceNet Command Application Suite is a Supervisory Control and Data Acquisition (SCADA) suite. It was developed specifically for interfacing through a DCD and to Thermon Control and Monitoring systems through industrial communication lines.

The Application Suite can be run from any computer connected to the database and communicates to the TraceNet DCD. Each application functions independently, allowing the user to customize reports and information much more readily.

SYSTEM REQUIREMENTS

Application Station:

CPU	800MHz or Faster
Operating System	Windows 7 or Better
Screen Resolution	1280 x 720
Available RAM	min 4GB
Free Hard Disk Space	min 512MB
Communication	Ethernet

Database Station:

CPU 1GHz or Faster, 4 Core	
O/S Windows Server, Linux	
Available RAM	min 4GB
Free Hard Disk Space	min 500GB
Communication	Ethernet

Communication:

TraceNet Command is specifically designed to communicate to Thermon Control and Monitoring systems through the DCD data communication device. Refer to the DCD specification sheet for more details.



FEATURES

- Simple coordination, organization, control, and monitoring of multiple heat tracing circuits
- The alarm list makes tracking and trending conditions in the plant easier using current and historical data
- Multivariable trending enables smoother and more functional Key Performance Indicator (KPI) development
- System scenario batch settings build for quick process or large scale operation changes
- SQL database allows efficient and reliable storage and access to data
- DCS integration for remote operations are made more efficient with TraceNet Command

European Headquarters: Boezemweg 25 • PO Box 205 • 2640 AE Pijnacker • The Netherlands • Phone: +31 (0) 15-36 15 370 Corporate Headquarters: 100 Thermon Dr • PO Box 609 • San Marcos, TX 78667-0609 • Phone: 512-396-5801 • 1-800-820-4328 For the Thermon office nearest you visit us at . . . www.thermon.com



PRODUCT SPECIFICATIONS **TraceNet™ Command** APPLICATION SUITE

USER INTERFACE

System Monitor – This application shows the timestamp of incoming data, both from the controller as well as the database. It also shows the synchronization of the system information across all operators, displaying when setpoints have changed and when they've been updated within the controllers.

Setpoint DB – This application offers the operator the ability to view and edit any setpoint of any controller or set of controllers. Setpoint Editor also enables the saving and implementing of scenarios or batch changes to a plant.

Circuit Viewer – This application sorts through the selected group of controller heat trace circuits, displaying graphically and numerically the setpoints for current, ground current, and alarms. It also allows the operator to review and change the status of the circuit.

Temperatures – This application graphically displays the temperatures for the selected group of heat traced piping or equipment.

Alarm Lists – This application allows an operator to view all alarms from all controllers within a plant, and to sort them by date, by function, or by circuit and controller.

Trend Plotter – This application tabulates and displays information in a line graph format. It allows the operator to view trends over time – or in coordination with other system variables in order for key performance indicators to be more easily detectable and tracked.



	+ 0	9.2.2.2.2.2	11/101	100		1.4		- 6	1001	1fage	(TO UNK	-
BHT, FSMB												
lanataa.	Serg		ununi.	depund	_	07	54					
- SESO 1 - SESO			1000			1 7.064 0071 0-Groat rumi				de las contra de las deservos		
70014 C/71-0	the second s	- 444	INS.	142		1 T004-0014-Gristman2				Matter -		
20054-0427-02	and the second se	41.0	Lawr .	1.00		1 7864 (XI) +6-Genet rund				lane .		
715014 CH7 18-18	100.0		10.54			A 72984 OF 14-Groat numi				Martin Contractor		
23X04 CHT 29-28	10.0		1546			a TRMA OFTA-Grant manh				Statute Lines		
725214 CHT 25-30			CAL.	18.2	_	6 7004 OF 14-Centered						
73504 CRT 30-38 	10.2				_	1 TBM/ OFT-L2-Circuit sum				Sector		
/03030 CH7 1-8	2004A		26.45	82						Weta		
71203 C47 7-12	1415		13.85	44		8 28664 CKF3132-Carout world				ante.		
705038 CKT 13-18	1017	416	14.115	75		8 T2NR4 OLD 3 32 CHOME HUME	F			State		
201000/03/118-24	The second se	8.1.0	14.1	1.0		28 TENSI OXT 3-12-Cecust north	18			Serve		
733038 CH7 25 30 735218 CH7 26-28 735218 CH7 27-42												
276032CK74248	20 5 0 1 05	S-12-012 (2%	CONSERVE TRANSPORT	01114-011								
715086 CHT 1-6 715066 CHT 7-82	Endad .					Pipe 2 Antipert		+ 13				-
735000 CH7 13-18	Abertan kerg			-96.0		High Exceed Maren	1948		Genuel Correct		38.0	
215068 CKT 18-34	Carlosi Bund			200.0	52	High Current Tile	16.0		High Ground Lu	nerd Alarm	288	
200068 CA7 25-30	High Temp Alarm			10.2	14	Paular Convert	13.40	- 12	High Ground Cu	unit Tala	38.0	
733586 C47 IR-36 725086 C47 IF-40	Figh Important Seco			116.0	161	Herler Curint Seen	28.81		Genuted Correct		32.0	
205080 CVT 41-48	High Tump Tra			220.2	161	Hatter Current Last	14.80	12				
= 10MPC					6	Los Carlest Alast		- 22				
20000BCN7 5-4	Ice Wep Heren			60.5	1.54	Low Current Alient	0.8	12				
735079 CK7 7-82	Low Verspectual Service			65.4	8			-14				
7/30/19/08/13-08 19/90/10/08/13-34	Temperature			200.J	8			8				
233000 (31 / 20 + 4) 23602 (30 + 24) 23302 (31 + 24) 23302 (31 + 24) 23302 (31 + 24) 23302 (31 + 24) 23302 (31 + 24) 23302 (31 + 24) 23302 (31 + 24) 23303 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24) 23305 (31 + 24)	* R	78 0 100 100 100 100				150 JR.8 7 7 9 137 137 0 137	5 PT 20			70 - 10 - 10	2	

Circuit Viewer App